

# Go Cat 3.2M

## SPECIFICATION SHEET



### DIMENSIONS

Length	3.20 m (10'6")	Height	0.60 m (2')
Beam	1.90 m (6'2")	Weight	35 kg (77 lbs)
Packed size	1.3 x 0.5 x 0.3 m (4'3"x 20"x 12")		
Tube diameter Main	0.47 m (19")	Number of tubes Main	4
Tube dia. Hijacker	0.14 m (5.5")	Number of tubes Hijacker	2
Tube volume total	1000 litres (35.3 cuft)		
Floor to water clearance (unladen)	150mm (6")		

### MATERIALS

Hulls outer	HF Welded, 840D Polyester Reinforced Polyurethane (590g/m <sup>2</sup> – 18oz/yard <sup>2</sup> ), Coating thickness 0.1mm both sides, Total material thickness 0.6mm
Bladder	HF Welded 0.25mm TPU (non reinforced polyurethane) with 2 way Boston valves
Transom	3mm powder coated Aluminium
Nose Cone	Foam/epoxy/fibreglass/EVA
Brackets	Fibreglass
Floor	Reinforced PVC/ PVC Foam/Epoxy/glass
Handles	EVA/UPVC/Nylon

### ENGINE SPECIFICATIONS

	REC	MAX
Size	15Hp	30Hp
Passengers	2	4
Weight	150 kg	300 kg
Top speed	25 knots	30 knots

### WARRANTY

Parts and labour	2 years
Material outer	3 years
Bladders	3 years

### COLOURS

White/Orange/Grey



White/Blue/Grey



White/Grey



ADR INTERNATIONAL PO Box 65 LADA KOMPLEX LANGKAWI MALAYSIA 07007



PH +60164667920

EMAIL INFO@ADR-GOCAT.COM

